

NeverStrip
FLOOR COATINGS

NeverStrip Color Sealer



NeverStrip Color Sealer

NeverStrip Color Sealer™ is a premium grade opaque grout sealant that is oil repellent, stain resistant, breathable, flexible, waterproof, color stable and non-yellowing. It contains granite resin for durability, modified densification agents for easy application and constant acting mildicides to help fight bacteria, mold and mildew. Available in many colors, this sealer will create a clean consistent appearance while providing ultimate protection for your grout.

Features

NeverStrip Color Sealer™ is a high performance industrial grout sealer.

- User-friendly, one-coat application.
- No harsh vapors or smells.
- Withstands up to 1200 psi pressure cleaning.
- Penetrates deep into grout for maximum sealing properties
- Extends the life expectancy, and integrity of grout.
- Creates an extremely durable stain resistant surface.
- Easy to maintain with green and LEED.
- Certified cleaners and methods.
- Resists strong cleaning compounds, alkalis, oils and many acids.
- Does not support mildew or fungi growth.
- Resists ultraviolet radiation.
- Helps prevent staining from waterborne contaminants.
- Finished appearance resembles actual grout.

Packaging

One Pint (16 oz) Round White Plastic Containers with Flip-Top Caps
/ Qty 4 to Case

Coverage (16 oz bottle)

Approximately 150 s/f for 1"-2" tile
with 1/8" Grout Line

Approximately 300 s/f for 12" tile
with 1/4" Grout Lines

***Coverage rate will vary with application, tile size and grout width.**

Physical Properties

Color: Varies

Form: Opaque thick solution

Topical: Yes

Flash Point: None

Freeze Point: 32°F(0°)

Shelf Life: 12 months in factory sealed container

Mixing and Application

Please note that NeverStrip Color Sealer™ is for professional use only by NeverStrip Certified Technicians. For more information, please consult with your NeverStrip Floor Coatings Representative.

Surface Preparation

- 1 Shake well before use.
- 2 When using more than one container of same color, combine containers and mix well to avoid color variation.
- 3 Grout should be clean and free of all contaminants, sealers and finishes that may inhibit bonding or absorption of color.
- 4 Once sealer and/or finish have been removed, use Deep Clean and then Grout Prep to clean and prep grout lines.
- 5 New grout must be cured at least 72 hours before application.
- 6 Non-polished and/or Unglazed tile should be sealed with Color Release before color application to avoid color absorption.
- 7 To confirm desired color, apply to small area and allow 6 hrs dry time.
- 8 Color can be applied to semi-dry grout lines.

Application for Tiled Surfaces with 1/8"- 3/16" Grout Lines (1"- 2" Tiles)

- 1 Apply 1 oz. of product over a 10 s/f area in an "S" motion using a squeeze applicator bottle.
- 2 Mist 10 s/f lightly with water (4-6 sprays from 3 ft. elevation).
- 3 Using a white buffing pad cut into 6" x 6" square, work color across surface and deep into grout lines (Don't worry about getting color on tile).
- 4 Use damp chamois cloths to remove excess color from tile surface by wiping with diagonal action.
- 5 Allow 8-10 minutes of dry time.
- 6 Buff color residue from tile surface using terry cloth or white buffing pads and a light mist of water as necessary.

NeverStrip Color Sealer

Application for Tiled Surfaces with 1/4" - 3/8" Grout Lines

- 1 Apply a small thin bead of product directly to the center of grout lines over 10 sq ft area.
- 2 Mist very lightly with water (1 spray from 3 ft. elevation).
- 3 Work back and forth with a small stiff bristled brush to assure a thin, even application (Do not allow it to bead or puddle).
- 4 Use damp chamois cloths to remove excess color from tile surface by wiping with diagonal action.
- 5 Allow 8-10 minutes of dry time.
- 6 Buff color residue from tile surface using terry cloth or white buffing pads and a light mist of water as necessary.

Dry Time

Ready for light traffic in 2 to 4 hrs. Resume normal traffic in 24 hours.
Do not expose to water (no mopping) for at least 24 hours.

Maintenance

Routine sweeping and mopping with water and neutral pH cleaners (if necessary) is recommended. Water only is sufficient for most environments.

DO NOT USE cleaners that are acidic or that have citrus (de-limonene) or Butyl compounds. Regular maintenance and cleaning will help appearance retention and prolong life of product.

Health and Safety Precautions

Eye contact: Check for and remove any contact lenses. In case of contact with eyes, rinse immediately with plenty of water. Seek medical attention if symptoms occur. **Skin contact:** Wash with soap and water. Seek medical attention if symptoms occur.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. Seek medical attention if symptoms occur.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Seek medical attention if symptoms occur.

Notes to Physician: No specific antidote. Medical staff must contact Poison Control Center.

NeverStrip
FLOOR COATINGS

Customer Service: 708.588.9707

NeverStrip Office, 111 S Grant St, Hinsdale, IL 60521

NeverStrip Warehouse, 9600 W Ogden Ave, La Grange, IL 60525

www.neverstrip.com

For Hazardous Materials (or Dangerous Goods) Incident:

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC, Day or Night, USA and Canada: 800.424.9300

Made in U.S.A./Fabriqué aux É.-U.