

NeverStrip™
FLOOR COATINGS

NeverStrip Liquid Grip™

Step 1 and 2



NeverStrip Liquid Grip

NeverStrip Liquid Grip™ is a high-traction, Micron-thin coating system for WET commercial applications. This rapid in-use, low-to-no odor system provides a durable, high-performance, non-yellowing and long-lasting surface in residential and commercial environments.

Liquid Grip can be applied onto virtually any hard flooring surface including: ceramic, porcelain, quarry tile, concrete, terrazzo, VCT, LVT, linoleum, rubber, cork, sheet vinyl and other coatings such as urethane, epoxy and wax.

Applications include restaurants, retail, restrooms, shower stalls, locker rooms, ramps, stairs, operating and emergency rooms and pool decks or anywhere higher traction is desired.

Liquid Grip™ is sold as a 2-quart kit.

Step 1 with NeverStrip Grip applied first. Step 2 applied as a sealer or topcoat.

Characteristics

- Non-yellowing.
- System has recorded a wet coefficient of friction of greater than .80 using a BOT 3000 COF Floor Tester.
- Two coat system; Step 1 with NeverStrip Grip and Step 2 sealer coat.
- Dries for second coat or light traffic in 10-15 minutes at 70 degrees and 50% humidity, respectively.
- Allow 8-hours after application before subjecting Liquid Grip to water.
- Clean with NeverStrip Micron Clean at 1-6 oz per gallon of water depending on cleaning demands.
- Not meant to be submerged for lengthy periods of time.
- Not designed for extensive use in commercial kitchens, food plants and heavy industrial applications.
- Do not machine scrub with a pad.
- Clean with a soft brush and extract for best results.
- Coverage of 1,000 to 1,250 sq ft per coat
- Available in Satin and a Low to Medium Gloss.
- No need to strip Liquid Grip in its normal life cycle but the product can be easily removed.
- Outstanding adhesion to virtually any hard flooring surface without abrasion to the surface or acid etching
- Use product within 12 months of purchase.

Coverage

Single applications of Step 1 and Step 2, respectively are expected to yield 1,000 to 1,250 sq ft per application per quart, depending on surface porosity.

Packaging

A kit consists of two 1 quart plastic bottles (0.946 liters) and two 9" high-density foam roller covers.

NeverStrip Liquid Grip

CAUTION

Do not use products containing d-Limonene or butyl.

NeverStrip recommends using NeverStrip Micron Clean™ for cleaning and maintaining Liquid Grip.

Liquid Grip is not freeze/thaw stable.

Do not use harsh chemical solvents to clean as they may damage or remove the coating.

Recommended storage temperature range is from 50°F to 80°F.

Wait 8 hours before using water on the coating.

Shelf life 12 months from purchase date. Seal container after each use.

Do not over apply Liquid Grip stay within recommended coverages.

Do not over work the product, Liquid Grip dries quickly.

Do not dilute.

Application

- 1** Surface should be dry clean and free of soil, grease, oils and other contaminants. Air and surface temperature should be 50°F to 90°F.
- 2** Shake Step One quart container well prior to each pour and/or use.
- 3** Pour the desired amount of product into an applicator tub. Dip and roll for best control of coverage rate. It is advised to use a sufficiently large applicator tub to allow for sufficient agitation with each dip of the roller cover. This process is critical to achieve an even distribution across the floor of the NeverStrip Grip aggregate.
- 4** Do not pour product onto the floor and spread. This method may result in excessive or uneven film thickness and/or uneven distribution of NeverStrip Grip Aggregate.
- 5** Apply Step 1: Dip and roll Step 1 from the applicator tub using a NeverStrip supplied high-density 9" foam roller cover to achieve 1,000 to 1,250 sq ft per quart per coat. If a second coat is desired, apply 10-15 minutes after the first coat of Step 1 and prior to application of Step 2.
- 6** Wait until Step 1 coat is dry to the touch-typically 10-15 minutes.
- 7** Apply Step 2, like Step 1 above using a "FRESH" not used foam roller cover.
- 8** Wait 10-15 minutes before walking on the surface or to open to foot traffic.

Cleaning, Maintenance and Removal

NeverStrip Liquid Grip, due to its textured nature, will attract and hold soil and oils. The surface must be cleaned regularly to dislodge or break down the buildup of contaminants, which may, over time, create discoloration on the surface and decrease the products slip properties.

NeverStrip Liquid Grip is best cleaned with soft nylon brushes and NeverStrip Micron Clean. This cleaner can be used for daily use at 1 oz/gallon of water or as a degreaser at 4- 6/oz/gallon of water. Scrubbing can be done with a deck brush or 175-rpm floor machine. Extraction after scrubbing will produce the best results.

Do not use a pad to clean Liquid Grip as the pad may wear down the NeverStrip Grip Aggregate.

Go to <http://www.neverstrip.com/clean-maintain.htm> for full cleaning and Maintenance instructions of NeverStrip's Micron coatings.

Liquid Grip does not need to be stripped or removed in its normal life cycle. It can be removed/stripped using the following procedures:

- 1) Scrub Liquid Grip using with water and a NeverStrip supplied EPP pad using a weighted oscillating floor machine, such as a Square Scrub or Tomcat, or
- 2) Scrub Liquid Grip using a weighted, 175-rpm floor machine with a NeverStrip supplied EPP pad or 3M SPP pad and Johnson/Diversey Pro Strip or equivalent at a 1:5 dilution ratio with water with 15 minute dwell time.

Health and Safety Precautions

KEEP OUT OF THE REACH OF CHILDREN.

NeverStrip Liquid Grip is an alkaline and may cause eye and skin irritation. Do not take internally. Avoid prolonged contact with skin. Avoid ingestion of material. If swallowed, do not induce vomiting - call physician.

Avoid contact with eyes. Protective clothing is recommended. Protective goggles are recommended in case of splashing. If splashed in eyes, wash immediately with clean water and call physician if irritation persists. Contact areas should be thoroughly washed with soap and water. Additional precautions, safety information and first aid treatments are contained in the Safety Data Sheet.



800.854.5414
orders@neverstrip.com
www.neverstrip.com

For Hazardous Materials (or Dangerous Goods) Incident:
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC, Day or Night USA and Canada
800.424.9300