

**NeverStrip™**  
FLOOR COATINGS

# NeverStrip™ Tile Seal™

A NeverStrip Micron Coating



# NeverStrip Tile Seal

1 of 2

NeverStrip Tile Seal is an ultra-clear, high performance, rapid drying, micron-thin, film forming surface treatment for ceramic, porcelain and brick flooring.

## Characteristics

- Single component product, no mixing, no pot life
  - Ideal for commercial and residential applications (indoor or outdoor/wet or dry) including: lobbies, restrooms, restaurants, shower walls and floors, pool decks, and locker rooms.
  - >.60 wet SCOF ( BOT 3000E Slip Meter)
  - VOC less than 50 g/l
  - 15 minute typical dry time between recoats and for light traffic after final application.
  - Low to no odor
  - Coverage is typically 1,000 to 1,500 sq ft per quart per application.
  - Volume solids - 23%
  - Excellent abrasion and stain resistance
  - Shelf life 12 months from NeverStrip ship date
- 
- Application of NeverStrip Color Sealer is recommended for grout lines prior to application of Tile Seal
  - Two (2) or three (3) thin applications are typical
  - Tile Seal is designed for use on ceramic, porcelain and brick surfaces in indoor and outdoor commercial and residential environments.
  - Available in satin sheen only; can be burnished for higher gloss levels
  - Do not clean or apply water to Tile Seal for 8 hours after application.

## Packaging

Quart (32 oz), white plastic bottle

## Coverage

Typical 1,000 to 1,500 sq ft per quart per application

## Surface Preparation

Remove any floor finish, soil, etc., and tack the floor with a NeverStrip supplied tack cloth to remove hair, lint, etc. from the floor. Surface should be dry and clean prior to proceeding. The use of NeverStrip Color Sealer in the grout lines is recommended prior to a Tile Seal application. Tile Seal will typically not by itself seal grout.

## Application

- 1 Tile surface must be dry before application
- 2 Shake before applying
- 3 Apply Tile Seal at 1,000 to 1,500 sq. ft. per quart per application. Coverage will vary depending on the porosity of the floor and the person doing the application.

### DO NOT APPLY TOO THICK AND DO NOT OVERWORK

- 4 Tile Seal is best applied on tile and grout floors by applying product onto the microfiber pad for every 24 sq ft (4 \* 6 foot sections) or spraying a light mist onto the floor with a pump-up sprayer and then spreading the product with a microfiber pad.

### DO NOT ALLOW TILE SEAL TO COME IN CONTACT WITH GLASS, FABRIC, METAL OR PAINTED SURFACES

- 5 Two or three thin applications of Tile Seal is typical. Allow each coat to dry before applying the next coat. Typically, Tile Seal will dry in 15 minutes or less.
- 6 If desired, buff or burnish Tile Seal after each application. Tile Seal does not need to be buffed or burnished. Without burnishing, a mid luster or satin sheen is typical of Tile Seal on ceramic or porcelain. Two or three applications of Tile Seal provides a medium or satin sheen without any burnishing.
- 7 Tile Seal applied too thick may become white and not properly cure. Tile Seal, as with all of NeverStrip Micron "Coatings, must be applied thin and within recommended coverage ranges with each application.
- 8 Tile Seal dries quickly. Do not over work the product. Do not over apply the product. Do not pour the product onto the floor and then spread. Do not apply the product with anything other than a looped, flat microfiber pad. Do not apply in sections larger than 24 sq ft at a time. Tile Seal for Dry Climates may be a desired choice for dry climates with low humidity.

# NeverStrip Tile Seal

2 of 2

## CAUTION

**Do not apply product heavier than a very thin film as recommended.**

**Do not overwork the product.**

**Use on interior surfaces only**

**Do not allow Tile Seal to come in contact with glass, fabric, metal or painted surfaces.**

**Do not clean or apply water to Tile Seal for at least 8 hours after application.**

**At low humidity environments streaking may occur. Consider using NeverStrip Tile Seal for Dry Climates.**

## For Industrial Use Only

Not for sale or resale to general public.

For NeverStrip Authorized Dealer  
Professional Use Only.

## Removal

The coating should not need to be removed in its normal life cycle. Tile Seal is removed using a butyl-based floor finish stripper with a black stripping pad or with a NeverStrip supplied EPP pad with a weighted oscillating floor machine, such as a Square Scrub. Follow standard procedures.

## Cleaning and Maintenance

Go to: [http://www.neverstrip.com/cms/wp-content/uploads/2018/10/Cleaning-Maintenance\\_Micron\\_2018-10.pdf](http://www.neverstrip.com/cms/wp-content/uploads/2018/10/Cleaning-Maintenance_Micron_2018-10.pdf)



800.854.5414  
orders@neverstrip.com  
www.neverstrip.com

**For Hazardous Materials (or Dangerous Goods) Incident:**  
Spill, Leak, Fire, Exposure, or Accident  
**Call CHEMTREC, Day or Night USA and Canada**  
800.424.9300